



GREASE APPLICATION GUIDE

For more information about pricing and additional product items, please contact your Super S Sales Representative.

Visit Our Facebook!
@SuperSGLOBAL



Visit Our Website!
www.SMITTYSINC.net



65415 HWY 51 North
Roseland, LA 70456
Comments/Questions 800-256-7575

NAME	APPLICATION								GREASE FEATURE										
	PLAIN BEARINGS	ROLLER BEARINGS	ENCLOSED GEARS	GEARED COUPLING	SLIDES, LINKAGES & PINS	ELECTRIC MOTORS	WIRE ROPES	OPEN GEARS	HIGH SPEED	LOW SPEED	HIGH TEMP.	LOW TEMP.	EXTREME PRESSURE	VIBRATION	WATER	SHOCK LOAD	LIFE	CONTAINS SOLIDS	PUMPABILITY
ISO 460 Hi-Temp w/ 3% Moly	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Super Blue EP2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Hi-Temp Red EP2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Calcium Sulfonate EP2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Marine Synthetic EP2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Super Moly EP2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MP2 Amber Lithium	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MP3 Amber Lithium	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Super MP2 Graphite	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MP2 Red Lithium	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MP2 Blue	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Multi-Purpose #2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
White Lithium EP2	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Cotton Picker Grease	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
"000" Grease	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Post Tension EP 1.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
WireSeal 680	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
WireSeal 1500	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
WireSeal 2500	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

● Outstanding performance in application ● Good performance in application ● Not suitable performance in application ● Not applicable



GREASE



SMITTYSINC.NET



SUPER S® SUPER CS EP2 SYNTHETIC GREASE

Super S® Super CS is among the highest performance of multi-purpose greases, it is formulated with premium high VI (Viscosity Index) oils, performance additives and a Calcium Sulfonate extreme pressure (EP), synthetic based thickener. It is world renowned for its unequalled corrosion properties as well as its Extreme Pressure properties and shear stability. It is specifically formulated for severe service, extreme environment and marine applications, and off-road machinery. It exceeds the requirements of all NLGI EP2 grease applications. Meets requirements of NLGI GC-LB.

PRODUCT	PACKAGING	PART #
CS EP2	50/14 oz	SUS 202
	35 lb Pail	SUS 202-35
	120 lb Keg	SUS 202-120
		SUS 202-400



SUPER S® SUPER MP2 GRAPHITE GREASE

Super S® Super MP2 is a graphite fortified multi-purpose 12-HSA NLGI #2 lithium grease that exhibits good mechanical stability, rust inhibition and water resistance. Use where a heavy grease with solid lubricants is required. Super S® MP2 Graphite Grease has broad application and may be more suitable for use in many cases than dry powered graphite or basic household oils. Meets requirements of NLGI GA-LA.

PRODUCT	PACKAGING	PART #
MP2 Graphite	50/14 oz	SUS 204



SUPER S® MARINE EP SYNTHETIC GREASE

Super S®Marine is a high performance Synthetic Extreme Pressure (EP) NLGI Grade #2 Calcium Sulfonate grease developed for Marine and other applications needing severe service properties and/or a high resistance to washout, water, moisture, rust and corrosion, including saltwater. It demonstrates exceptional anti-wear and extreme pressure properties, oxidation and shear stability, and provides outstanding low and high temperature performance. Meets requirements of NLGI GC-LB.

PRODUCT	PACKAGING	PART #
Marine	18/3 oz	SUS 205-03
	50/14 oz	SUS 205



SUPER S® HI-TEMP RED #2 EP LITHIUM GREASE

Super S®Hi-Temp Red is a 12-HSA premium NLGI#2 extreme pressure (EP), multi-purpose, lithium complex grease that provides outstanding high temperature performance and excellent lubrication over a wide temperature range and a variety of services including heavy duty fleet, automotive, farm and industrial applications. It provides excellent water resistance, rust and corrosion protection, and oxidation resistance. It provides wear protection under extreme loads, resists separation, and resists softening due to heat. The Lithium Complex thickener gives it a dropping point in excess of 500°F. Meets requirements of NLGI GC-LB.

PRODUCT	PACKAGING	PART #
Hi-Temp Red	10/14 oz	SUS 67-10
	50/14 oz	SUS 67
	12/1 lb	SUS 77
	6/4 lb	SUS 67-4
	35 lb Pail	SUS 71
	120 lb Keg	SUS 70
	400 lb Drum	SUS 78



SUPER S®MULTI-PURPOSE #2 (MP2) GREASE

Super S®MP2 is a NLGI#2 lithium based, water resistant grease for automotive and light to medium trucks, farm and industrial applications. It is recommended for automotive chassis lubrication points, ball joints and universal joints. It resists softening at high operating temperatures, seals out dirt and moisture contamination, is formulated with rust and oxidation inhibitors, and offers good stability over its operating range. Super S®MP2 provides excellent water resistance, is shear stable and provides good anti-wear protection. Meets requirements of NLGI GB.

PRODUCT	PACKAGING	PART #
Multi Purpose	18/3 oz	SUS 66-03
	10/14 oz	SUS 66-10
	50/14 oz	SUS 66
	12/1 lb	SUS 66-1
	35 lb Pail	SUS 68
	120 lb Keg	SUS 69
	400 lb Drum	SUS 79

ALSO AVAILABLE IN:



PRODUCT	PACKAGING	PART #
MP2 RED	50/14 oz	SUS 66-14
	12/1 lb	SUS 66-12
	35 lb Pail	SUS 66-35
	120 lb Keg	SUS 66-120
	400 lb Drum	SUS 66-400



PRODUCT	PACKAGING	PART #
MP2 AMBER	50/14 oz	SUS 68-14
	12/1 lb	SUS 68-12
	35 lb Pail	SUS 68-35
	120 lb Keg	SUS 68-121



SUPER S® “00” COTTON PICKER SPINDLE GREASE

Super S®“00” is a smooth textured, corrosion preventive NLGI 00 lithium grease based upon the best time-tested formulations specifically developed for lubricating modern cotton picker spindle assemblies. It is manufactured with a special low viscosity, low pour point base oil to provide low friction, excellent penetration, full protection and efficient operation in both hot and cold weather.

PRODUCT	PACKAGING	PART #
“00”	12/1 Qt	SUS 111
	35 lb Pail	SUS 114
	120 lb Keg	SUS 116
	400 lb Drum	SUS 117

SUPER S® COTTON PICKER SPINDLE CLEANER

Super S® Cotton Picker Spindle Cleaners is a top quality oil emulsion based upon the time-tested formulation specifically developed for cleaning modern cotton picker spindles. Super S®Spindle Cleaner is a water soluble oil-based liquid that mixes well with water of any hardness and cleans dirt, plant materials, and other foreign contaminants from cotton picker spindles. It applies a protective film as it washes the spindle and is compatible with spindle grease. It won't wash spindle grease out of the critical areas it's lubricating, but will still coat those parts to protect them. It also keeps moisture pads from drying out and hardening, and helps to keep doffers in good condition.

PRODUCT	PACKAGING	PART #
Spindle Cleaner	5 Gal	SUS 123
	55 Gal	SUS 124

SUPER S® POST TENSION GREASE

Super S® Post Tension Grease is premium 12-HSA lithium based grease specially formulated for the Post Tensioning construction industry. It exceeds the post Tensioning Institutes (PTI) specifications for corrosion protection of unbonded and single-bonded tendons in corrosive service. Graded to a NLGI 1.5 consistency and fortified with a robust corrosion inhibitor package which exhibits superb protection against oxidation.

PRODUCT	PACKAGING	PART #
Tension Tension	Tote	SUS 700-400
	Bulk	SUS 206 Bulk



SUPER S®SUPER BLUE EP2 HI-TEMP GREASE

Super S® Super Blue is a 12-HSA high performance, extreme pressure (EP), multi-purpose grease formulated for demanding high temperature applications dropping point exceeds 500°F. Super S® Super Blue EP2 reduces friction with a unique formulation that adheres to metallic surfaces (versus plating out) to reduce the highly localized heating and wear of metal surfaces. It is fortified with extra EP additives to withstand extreme loading and shock loads. Exceeds the latest equipment requirements. Meets requirements of NLGI GC-LB.

PRODUCT	PACKAGING	PART #
Blue EP2	50/14 oz	SUS 201
	35 lb Pail	SUS 201-35
	120 lb Keg	SUS 201-120
		SUS 201-400

SUPER S® SUPER MOLY EP2 GREASE

Super S® Super Moly is a 12-HSA high performance NLGI#2 multi-purpose grease provides additional wear protection under extreme/severe loads with enhanced extreme pressure (EP) and film properties, and outstanding high temperature performance with a dropping point in excess of 500°F. It is fortified with molybdenum disulfide which reduces the coefficient of friction, protects against localized heating and wear of metal surfaces and provides exceptional film strength, making it especially good for shock loads and low speed, heavy load applications such as in heavy construction and earth moving equipment. Meets requirements of NLGI GC-LB.

PRODUCT	PACKAGING	PART #
Moly EP2	50/14 oz	SUS 203
	35 lb Pail	SUS 203-35
	120 lb Keg	SUS 203-120

