

# MOTOROILS

SMITTYSINC.NET





## SUPER S® SUPERSYN™ FULL SYNTHETIC MOTOR OIL

Super S® SuperSyn™ is a 100% full synthetic motor oil engineered with the latest lubricant technology to provide the ultimate in engine protection and performance. Engineered for gasoline engines to provide superior protection against engine wear, eliminate LSPI occurrence, formation of sludge and extreme high temperatures which can cause conventional oils to break down. Compatible with all conventional and synthetic oils.

**0W-16 Meets or exceeds:** API SP • ILSAC GF-6B

**0W-20, 5W-20, 5W-30, 10W-30 Meets or exceeds:** API SP • ILSAC GF-6A

**0W-40, 5W-40 Meets or exceeds:** API SP

| PRODUCT      | PACKAGING | PART #     |
|--------------|-----------|------------|
| <b>0W-20</b> | 6/1 Qt    | SUS 795    |
|              | 3/5 Qt    | SUS 79505  |
|              | 6 Gal     | SUS 6795   |
|              | 55 Gal    | SUS 795-55 |
| <b>5W-30</b> | 6/1 Qt    | SUS 796    |
|              | 3/5 Qt    | SUS 79605  |
|              | 6 Gal     | SUS 6796   |
|              | 55 Gal    | SUS 796-55 |

| PRODUCT       | PACKAGING | PART #     |
|---------------|-----------|------------|
| <b>0W-16</b>  | 6/1 Qt    | SUS 797    |
|               | 6 Gal     | SUS 6801   |
| <b>0W-40</b>  | 6/1 Qt    | SUS 401    |
|               | 6 Gal     | SUS 60401  |
| <b>5W-20</b>  | 6/1 Qt    | SUS 393    |
|               | 3/5 Qt    | SUS 39305  |
|               | 6 Gal     | SUS 6393   |
|               | 55 Gal    | SUS 393-55 |
| <b>5W-40</b>  | 6/1 Qt    | SUS 397    |
|               | 3/1 Gal   | SUS 397-3  |
|               | 55 Gal    | SUS 399    |
| <b>10W-30</b> | 6/1 Qt    | SUS 350    |
|               | 6 Gal     | SUS 60350  |
|               | 55 Gal    | SUS 353    |



**SUPER S® EURO SUPERSYN™ FULL SYNTHETIC MOTOR OIL**

Super S® Euro SuperSyn™ Motor Oil is a full synthetic Mid SAPS engine oil formulated to meet the ACEA C3-16 technical requirements of the most demanding automobile manufacturers including General Motors, BMW, Volkswagen, Mercedes-Benz, and Honda/ Kia. Provides unmatched protection under the most severe conditions including sports driving, city and motorway, off road, and is suitable for use in both gas & diesel engines.

**5W-30 & 5W-40 Meets or exceeds:**

Euro SuperSyn™ 5W-30 Motor Oil are specifically designed for use wherever ACEA C3-16 or API-SN/CF or previous motor oil specifications are called for. Euro C3 also meets the performance requirements of the following OEMs: MB 229.51, MB 229.31, Porsche C30, dexos 2™, JASO DL-1, PSA B71 2288, VW 504.00/507.00, VW 502.00, VW 503.01(OBSOLETE)

**ACEA C3-16**

| PRODUCT | PACKAGING | PART #     |
|---------|-----------|------------|
| 5W-30   | 6/1 Qt    | SUS 394    |
|         | 6 Gal     | SUS 60394  |
|         | 55 Gal    | SUS 394-55 |
| 5W-40   | 6/1 Qt    | SUS 398    |
|         | 6 Gal     | SUS 60398  |
|         | 55 Gal    | SUS 398-55 |



**SUPER S® EURO SUPERSYN™ FULL SYNTHETIC MOTOR OIL**

Super S® Euro SuperSyn™ Full Synthetic Motor Oil provides among the highest levels of performance and protection ever offered in passenger car motor oils (PCMOs) by using newly developed additive technology and formulations of 100% synthetic base oils. They are licensed as API SL and meets the latest (2011) fuel economy standards while dramatically exceeding specifications for wear control, piston deposits, cleanliness, varnish and sludge, oxidation control, and emission system and seal compatibility. European classifications: ACEA A3/B4-16, BMW Longlife-01, MB P229.3/229.5, VW 502.00/505.01, RN 0700/0710, PSA B71 2296, and API SL/CF and is suitable for use in Ford WSS-M2C913-C.

**ACEA A3/B4-16**

| PRODUCT | PACKAGING | PART #     |
|---------|-----------|------------|
| 5W-30   | 6/1 Qt    | SUS 395    |
|         | 6 Gal     | SUS 60395  |
|         | 55 Gal    | SUS 395-55 |
| 5W-40   | 6/1 Qt    | SUS 396    |
|         | 6 Gal     | SUS 60396  |
|         | 55 Gal    | SUS 396-55 |



## SUPER S® MULTI-FLO® MOTOR OIL

Super S® Multi-Flo® Motor Oils are formulated to provide the highest levels of performance and protection in passenger car motor oils (PCMO). They meet the latest fuel economy standards while exceeding the car manufacturer's ILSAC GF-6A standards for wear control, piston deposits, cleanliness, varnish, sludge, oxidation control, emission system and seal compatibility. Super S® Multi-Flo® SN Motor Oils in grades SAE 30 and SAE 40 are formulated with synthetic blend motor oils.

- LSPI protection
- Fuel economy gains
- Low oil consumption
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection
- Excellent protection from deposits at all operating temperatures
- Excellent cold cranking capabilities
- Up to 40% cleaner pistons than the industry standard
- Extremely low volatility providing extended drain protection
- Compatible with conventional motor oils

### 5W-20, 5W-30, 10W-30 Meets or exceeds:

API SPS • ILSAC GF-6A

### 10W-40, 20W-50, SAE 30, SAE 40 Meets or exceeds:

API SP

# YOU'RE #1 CHOICE FOR SYNTHETIC BLEND MOTOR OILS!

| PRODUCT       | PACKAGING | PART #      | PRODUCT       | PACKAGING | PART #     |
|---------------|-----------|-------------|---------------|-----------|------------|
| <b>5W-20</b>  | 12/1 Qt   | SUS 121     | <b>10W-40</b> | 12/1 Qt   | SUS 51     |
|               | 3/5 Qt    | SUS 12105-3 |               | 3/1 Gal   | SUS 51-3   |
|               | 6 Gal     | SUS 6121    |               | 3/5 Qt    | SUS 5105-3 |
|               | 55 Gal    | SUS 121-55  |               | 6 Gal     | SUS 651    |
| <b>5W-30</b>  | 12/1 Qt   | SUS 93      | <b>20W-50</b> | 55 Gal    | SUS 60     |
|               | 3/1 Gal   | SUS 93-3    |               | 12/1 Qt   | SUS 48     |
|               | 3/5 Qt    | SUS 9305-3  |               | 3/1 Gal   | SUS 48-3   |
|               | 6 Gal     | SUS 693     |               | 3/5 Qt    | SUS 4805-3 |
| <b>10W-30</b> | 55 Gal    | SUS 93-55   |               | 6 Gal     | SUS 648    |
|               | 12/1 Qt   | SUS 50      |               | 55 Gal    | SUS 48-55  |
|               | 3/1 Gal   | SUS 50-3    | <b>SAE 30</b> | 12/1 Qt   | SUS 49     |
|               | 3/5 Qt    | SUS 5005-3  |               | 55 Gal    | SUS 64     |
|               | 5 Gal     | SUS 76      | <b>SAE 40</b> | 12/1 Qt   | SUS 98     |
|               | 6 Gal     | SUS 650     |               |           |            |
|               | 55 Gal    | SUS 59      |               |           |            |



## SUPER S® MULTI-FLO® HIGH MILEAGE MOTOR OIL

Super S® Multi-Flo® High Mileage Motor Oil is specially formulated to help extend the life of higher mileage engines. The high mileage additive is strengthened with seal conditioning agents to target problems such as oil leaks, oil consumption and sludge build-up. Multi-Flo® High Mileage Motor Oil meets the latest fuel economy standards while exceeding the industry standards for wear control, piston deposits, cleanliness, sludge, oxidation control, emission systems and seal compatibility.

Multi-Flo® High Mileage Motor Oil meets or exceeds the latest American Petroleum Institute (API) SP, and car manufacturers' ILSAC GF-6A classifications as well as all previous service classifications.

### Meets or exceeds:

API SP • ILSAC GF-6A

| PRODUCT       | PACKAGING | PART #    |
|---------------|-----------|-----------|
| <b>5W-20</b>  | 3/5 Qt    | SUS 1584  |
|               | 6 Gal     | SUS 61584 |
| <b>5W-30</b>  | 12/1 Qt   | SUS 1581  |
|               | 3/5 Qt    | SUS 1585  |
|               | 6 Gal     | SUS 61581 |
| <b>10W-30</b> | 12/1 Qt   | SUS 1580  |
|               | 3/5 Qt    | SUS 1586  |
|               | 6 Gal     | SUS 61580 |
| <b>10W-40</b> | 12/1 Qt   | SUS 1582  |
|               | 6 Gal     | SUS 61582 |

**Custom  
PLUS™**



## SUPER S® CUSTOM PLUS™ MOTOR OIL

Super S® Custom Plus™ Motor Oils feature premium base oils in formulation with proven high-quality anti-wear additives. This oil is designed for use in gasoline engines, combining versatility, heavy-duty engine protection and cost effectiveness into one motor oil. It is formulated with high levels of dispersant and detergent additives that effectively control sludge and varnish to help prevent corrosion, wear and deposits.

| PRODUCT       | PACKAGING | PART #     |
|---------------|-----------|------------|
| <b>5W-20</b>  | 12/1 Qt   | CUS 98201  |
| <b>5W-30</b>  | 12/1 Qt   | CUS 98202  |
| <b>10W-30</b> | 12/1 Qt   | CUS 98203  |
|               | 55 Gal    | CUS 204-55 |
| <b>20W-50</b> | 12/1 Qt   | CUS 98205  |
|               | 5 Gal     | CUS 205-5  |
|               | 55 Gal    | CUS 205-55 |



SUPER S® CUSTOM PLUS™ MOTOR OIL

Super S® Custom Plus™ Motor Oil is manufactured with high quality base oils and fortified with an anti-foaming additive for extra lubrication at an economical price. Super S® Custom Plus™ Motor Oil meets or exceeds car manufacturers' warranty requirements where an API Service SF/CF motor oil is recommended. It provides economical lubrication for older cars in light duty service which do not require high performance oils. Always consult your owner's manual for proper recommendations.

| PRODUCT | PACKAGING | PART #    |
|---------|-----------|-----------|
| SAE 30  | 55 Gal    | CUS 98352 |
|         | 12/1 Qt   | CUS 98354 |
|         | 3/1 Gal   | CUS 98355 |
|         | 5 Gal     | CUS 98356 |
| SAE 40  | 55 Gal    | CUS 98357 |
|         | 12/1 Qt   | CUS 98358 |
|         | 3/1 Gal   | CUS 98359 |
|         | 5 Gal     | CUS 98360 |
| SAE 50  | 55 Gal    | CUS 98361 |

NON-DETERGENT



SUPER S® NON-DETERGENT MOTOR OIL

Super S® Non-Detergent Motor Oils are manufactured with a quality base oil and fortified with an anti-foaming additive for engine lubrication at an economical price. These are for engines that do not require a high-detergent motor oil. They may be used where equipment suppliers call for a non-detergent motor oil with API SB requirements.

**CAUTION:** This oil is rated API SB and is not suitable for use in most gasoline powered automotive engines built after 1951. Use in more modern engines may cause unsatisfactory performance or equipment harm.

| PRODUCT | PACKAGING | PART #     |
|---------|-----------|------------|
| SAE 10  | 12/1 Qt   | SUS 84     |
|         | 3/1 Gal   | SUS 84-3   |
|         | 5 Gal     | SUS 7      |
| SAE 20  | 12/1 Qt   | SUS 85     |
|         | 55 Gal    | SUS 85-55  |
|         | 55 Gal    | SUS 93-55  |
| SAE 30  | 12/1 Qt   | SUS 41     |
|         | 2 Gal     | SUS41-2    |
|         | 5 Gal     | SUS 10     |
| SAE 40  | 55 Gal    | SUS 16     |
|         | 12/1 Qt   | SUS 45     |
|         | 3/1 Gal   | SUS 45-3   |
|         | 3/5 Qt    | SUS 4505-3 |
|         | 5 Gal     | SUS 11     |
| SAE 50  | 55 Gal    | SUS 11-55  |
|         | 12/1 Qt   | SUS 86     |
|         | 3/1 Gal   | SUS 86-3   |
|         | 3/5 Qt    | SUS 8605-3 |
|         | 5 Gal     | SUS 86-5   |

---

For more information about pricing and additional product items, please contact your Super S Sales Representative.

---

Visit Our Facebook!  
**@SuperSGLOBAL**



Visit Our Website!  
**[www.SMITTYSINC.net](http://www.SMITTYSINC.net)**



65415 HWY 51 North  
Roseland, LA 70456  
Comments/Questions 800-256-7575