

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Super Power Truck Wash

Synonyms: none

1.2. Intended Use of the Product

Concentrated all purpose cleaner

1.3. Name, Address, and Telephone of the Responsible Party

Company

Smitty's Supply, Inc.

PO BOX 530

Roseland, LA 70456

985-748-8214

www.smittysinc.net

1.4. Emergency Telephone Number

Emergency Number : 1-800-424-9300, CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Acute Toxicity, Inhalation, 4	H332
Eye Irritation, 2A	H312
Acute Toxicity, Oral, 4	H302
Serious Eye Damage, 1	H318
Skin Irritation, 2	H315

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H302 + H312 + H332: Harmful if swallowed in contact with skin or if inhaled.
H318: Causes Serious Eye Damage
H315: Causes Skin irritation

Precautionary Statements (GHS-US)

: Prevention

P280, P264, P270: Wear protective gloves/ protective clothing/ eye protection/ face protection. Wash hands and any affected exposed skin/ clothing thoroughly after handling. Do not eat, drink, or smoke, when using this product.

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



Precautionary Statements (GHS-US) : Response

Cont.

P301 + P312, P330, P305 + P351 + P338, P337 + P313, P302 + P 352, P362, P332 + P313, P304 + P340, P310, P321: IF SWALLOWED: Call POISON CENTER if you feel unwell. Rinse Mouth. IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/ attention. IF INHALED: Remove victim to fresh air and keep at rest in a position conformable for breathing. Immediately call a POISON CENTER. Specific Measures (see supplemental first aid instructions on this label.)

Storage

P403 + P235: Store in a well-ventilated place keep cool.

Disposal

P501: Dispose of contents/container in accordance with all local/ regional/ national/ international regulations.

2.3. Other Hazards

None Known

2.4. Unknown Acute Toxicity (GHS-US)

None of this product contains unknown acute toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Alcohols, C9-11, ethoxylated	(CAS No) 68439-46-3	10 - 15	H302: Harmful if swallowed H318: Causes Serious Eye Damage
2-butoxyethanol; ethylene glycol monobutyl ether butyl cellosolve	(CAS No) 111-76-2	40 – 50	H227: Combustible Liquid H302 + H312 + H332: Harmful if swallowed, in contact with skin or if inhaled H315: Causes Skin Irritation H319: Causes serious eye irritation

*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

3.2. Mixture

Not Applicable

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin Contact: Wash skin thoroughly with soap and water or use recognized skin cleanser. Continue to rinse for at least 10 minutes. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.

Ingestion: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: see below

Inhalation: May cause drowsiness and dizziness, nausea or vomiting, headache, drowsiness/fatigue.

Skin Contact: Causes skin irritation, redness

Eye Contact: Pain or irritation, watering, redness

Ingestion: Harmful if swallowed, nausea or vomiting

Chronic Symptoms: No known significant effects or critical hazards.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam for extinction.

Unsuitable Extinguishing Media: None noted

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: During a fire irritating or toxic decomposition products may be generated. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Explosion Hazard: Product is not an explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



Additional Hazards When Processed: Put on appropriate personal protective equipment (see Section 8). Do not swallow.

Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Empty containers retain product residue and can be hazardous. Do not reuse container.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container tightly closed and sealed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Do not store in unlabeled containers. Use proper containment to avoid environmental contamination.

Incompatible Materials: strong oxidizing materials

7.3. Specific End Use(s)

Concentrated all purpose cleaner

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

2-butoxyethanol; ethylene glycol monobutyl ether butyl	
ACGIH	TWA: 20 ppm
OSHA Z-1	TWA: 50 ppm TWA: 240 mg/m ³
NIOSH REL	TWA: 5 ppm TWA: 24 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. The engineering controls also need to keep gas, vapor or dust concentration below any lower explosive limits. Use explosion-proof ventilation equipment. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves. Practice safe glove removal to avoid skin contact with this product.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing. When there is a risk of ignition from static electricity, wear anti-static protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable limits. Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Blue
Odor	: Neutral
Odor Threshold	: Not available
pH	: 7.0
Evaporation rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 210 °F
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.083
Solubility	: Infinite
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Viscosity, Kinematic	: Not available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** No specific test data related to reactivity available for this product or its ingredients.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Under normal condition of storage and use, hazardous reactions will not occur.
- 10.4. Conditions to Avoid:** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
- 10.5. Incompatible Materials:** strong oxidizing materials
- 10.6. Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity:

LD50 and LC50 Data:

Alcohols, C9-11, ethoxylated	
LD50 Oral Rat	> 1400 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg
2-butoxyethanol; ethylene glycol monobutyl ether butyl	
LD50 Oral Rat	1746 mg/kg
LD50 Dermal Rabbit	435 mg/kg

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



Skin Corrosion/Irritation, Eye Damage/Irritation: Causes Eye Damage.

Respiratory or Skin Sensitization: Toxic in contact with skin. Causes skin irritation.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not Classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not Classified

Symptoms/Injuries After Inhalation: May cause drowsiness and dizziness. Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo

Symptoms/Injuries After Skin Contact: Repeated or prolonged skin contact may cause irritation. Adverse symptoms may include the following: irritation, redness

Symptoms/Injuries After Eye Contact: Direct contact with the eyes is likely irritating. Adverse symptoms may include the following: Can cause pain, watering, and redness.

Symptoms/Injuries After Ingestion: Adverse symptoms may include the following: nausea or vomiting

Chronic Symptoms: Not Classified

11.2. Information on Toxicological Effects - Ingredient(s)

See 11.1

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General:

Ingredient name	Result	Species	Exposure
2-butoxyethanol; ethylene glycol monobutyl ether butyl			
	Acute LC50 1550 mg/l	Daphnia	48 hours
	Acute EC50 1840 mg/l	Algae	72 hours
	Acute LC50 1474 mg/l	Fish	96 hours
	Chronic NOEC >100 mg/l	Fish	21 days

12.2. Persistence and Degradability: Not Classified

12.3. Bioaccumulative Potential: Not Classified

12.4. Mobility in Soil: Not Classified

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way. Do not empty into drains. Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

Not Regulated for transport

Special Precautions to the user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

05/22/2015

EN (English US)

Page 6 of 8

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
SARA Section 313 Form R Reporting	111-76-2 40 – 50 %

15.2. US State Regulations

[California Prop. 65](#)

This product does not contain any chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

15.3. Canadian Regulations

This material is listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 05/22/2015
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H332	Harmful if inhaled
H302	Harmful if swallowed
H312	Harmful if in contact with skin
H318	Causes serious eye damage
H319	Causes eye irritation
H315	Causes skin irritation
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection. W
P264	Wash hands and any affected exposed skin/ clothing thoroughly after handling.
P270	Do not eat, drink, or smoke, when using product.
P301 + P312	IF SWALLOWED: Call a POISON CENTER if you feel unwell.
P330	Rinse Mouth
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue Rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P362	Take contaminated clothing and wash before reuse.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P304 + P340	IF INHALED: Remove the victim to fresh air and keep at rest in a position comfortable for breathing.
P310	Immediately call a POISON CENTER
P321	Specific Measures (see supplemental first aid instructions on this label.)
P403 + P235	Store in well-ventilated place. Keep Cool.

Super Power Truck Wash

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Version SEA7.001



P501	Dispose of contents/container in accordance with all local/regional/ national/ international regulations.
------	---

Party Responsible for the Preparation of This Document

Smitty's Supply, Inc.

PO BOX 530

Roseland, LA 70456

985-748-8214

www.smittysinc.net

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2