

Super S[®] Concrete Form Oil

TECHNICAL PRODUCT INFORMATION



Super S Concrete Form Oil

Super S Concrete Form Oil is compounded to prevent bonding between steel or wooden forms and freshly poured concrete surfaces

FEATURES/ BENEFITS

Super S Concrete Form Oil

- Works on steel, wood, Teflon coated forms
- Works on mold surfaces used in concrete pre-cast operations
- Enhances stripability of forms
- Extend form life by protecting wood and preventing rust on metal
- Non staining
- Applied by spraying, mopping, dipping, or rolling

APPLICATIONS

- Forms and molds that need some release agent on them
- Concrete forming operations using wood or metal forms
- Pre-cast concrete

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling that you would use with petroleum products.

TYPICAL CHARACTERISTICS

Super S [®] Concrete Form Oil		
<i>Properties</i>	<i>Test Method ASTM D</i>	<i>Data</i>
Gravity, °API	1298	33
Flash Point °C/°F,	92	216/420
Pour Point °C/°F	97	-15/+5
Viscosity cSt @ 40°C	445	12

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 195

55 gallon drum