



### **SUPER S® ROCK DRILL OIL**

Super S® Rock Drill Oils are extreme pressure lubricants designed for the lubrication of air powered tools, such as jack hammers, rock drills, pneumatic construction and mining equipment under both wet and dry conditions. It has outstanding stability, adhesiveness, and excellent load-carrying capacity. They contain rust and oxidation inhibitors, EP additives, and a tackifier agent that protects the critical components of the tools.

PRODUCT	PACKAGING	PART #
<b>ISO 68</b>	55 Gal	SUS 190
<b>ISO 100</b>	5 Gal	SUS 309
	55 Gal	SUS 310

*(More products are also available. Please contact your sales rep for more information)*



### **SUPER S® SAWGUIDE OIL**

Super S® Saw Guide Oil is formulated with premium base stocks and additive with tackifier for excellent rust and corrosion protection. The premium fluid creates a boundary layer between the blade and guide reducing friction and heat while protecting critical components of the operation.

PRODUCT	PACKAGING	PART #
<b>ISO 100</b>	55 Gal	SUS 194

*(Also available in 150, ask your sales rep for more information)*



### **SUPER S® DRIP OIL**

Super S® Drip Oils utilize premium paraffinic base stocks and are clear, to a slight straw color. They are recommended for use on vertical shaft driven pumps equipped with a drip oiler. They are free of harmful additives, and their high viscosity index allows consistent flow with temperature variation.

PRODUCT	PACKAGING	PART #
<b>Drip Oil</b>	3/2 Gal	SUS 196
	5 Gal	SUS 36 DO
	55 Gal	SUS 37 DO

For more information about pricing and additional product items, please contact your Super S Sales Representative.

Visit Our Facebook!  
**@SuperSGLOBAL**



Visit Our Website!  
**www.SMITTYSINC.net**



65415 HWY 51 North  
Roseland, LA 70456  
Comments/Questions 800-256-7575

# INDUSTRIAL HYDRAULICS

SMITTYSINC.NET



### SUPER S® SUPERDRAULIC™ AW HYDRAULIC FLUID

Super S® SuperDraulic™ Premium AW Hydraulic Fluid is an extended drain, heavy-duty anti-wear hydraulic oil formulated with high VI paraffinic base oils and an advanced additive package to provide superior oxidation and thermal stability for (ASTM D-943) 5000+ hour service. It provides excellent water separation and demulsibility, and is specially formulated to suppress foaming while also allowing rapid air release, improving hydraulic system performance and helping to prevent pump cavitation. It protects system components from rust and corrosion.

PRODUCT	PACKAGING	PART #
<b>ISO 32</b>	5 Gal	SUS 161
	55 Gal	SUS 162
<b>ISO 46</b>	5 Gal	SUS 164
	55 Gal	SUS 163
<b>ISO 68</b>	5 Gal	SUS 166
	55 Gal	SUS 167
<b>ISO 100</b>	55 Gal	SUS 169

### SUPER S® ANTI-WEAR HYDRAULIC FLUID

Super S® AW Hydraulic Oils are general purpose, antiwear, rust, corrosion and oxidation inhibited oils with an anti-foam additive. They are suitable for use where service requirements are normal to moderate and long term, heavy-duty wear protection is not critical.

**Recommended for:**  
Sperry Vickers M-2950-S & I-286-S  
Denison HF-0, HF-1 & HF-2  
Cincinnati Milacron P-68, P-69 & P-70

PRODUCT	PACKAGING	PART #
<b>ISO 22</b>	5 Gal	SUS 222
	55 Gal	SUS 222-55
<b>ISO 32</b>	3/1 Gal	SUS 36-3
	5 Gal	SUS 36
	55 Gal	SUS 37
<b>ISO 46</b>	3/1 Gal	SUS 38-3
	5 Gal	SUS 38
	55 Gal	SUS 63
<b>ISO 68</b>	3/1 Gal	SUS 40-3
	5 Gal	SUS 40
	55 Gal	SUS 43
<b>ISO 100</b>	5 Gal	SUS 100
	55 Gal	SUS 100-55



### SUPER S® PREMIUM R & O TURBINE OIL

Super S® Premium R&O is a premium rust and oxidation inhibited formulation of paraffinic base oils blended with a carefully balanced additive system to achieve a combination of excellent water demulsibility, oxidation stability, and air release. Super S® Premium R&O Turbine Oils are designed for long life service protecting against system rusting caused by water contamination, and against sludge and deposits caused by oil oxidation. Available in viscosity grades ISO VG22 to ISO VG320.

PRODUCT	PACKAGING	PART #
<b>Turbine 32</b>	5 Gal	SUS 61
	55 Gal	SUS 62
<b>Turbine 46</b>	5 Gal	SUS 15
	55 Gal	SUS 47
<b>Turbine 68</b>	5 Gal	SUS 13
	55 Gal	SUS 14

### SUPER S® R & O HYDRAULIC OIL

Super S® R & O is a general purpose hydraulic oil that protects against rust, oxidation, corrosion and foaming in a wide variety of applications where service is light to moderate and anti-wear or extreme pressure properties are not required.

PRODUCT	PACKAGING	PART #
<b>ISO 32</b>	3/1 Gal	SUS 23-3
	5 Gal	SUS 1
	55 Gal	SUS 3
<b>ISO 68</b>	5 Gal	SUS 2
	55 Gal	SUS 2-55



### SUPER S® MINING HYDRAULIC OIL

Super S® Mining Hydraulic Oil is blended from well-refined base stocks to provide anti-wear lubricating properties primarily in mining applications. It is formulated with select additives to provide anti-rust and anti-oxidation performance. To meet requirements of the mining industry, this product is packaged in square metal cans.

PRODUCT	PACKAGING	PART #
<b>ISO 68</b>	35 lb Pail	SUS 40M
<b>ISO 100</b>	35 lb Pail	SUS 100M
<b>ISO 150</b>	35 lb Pail	SUS 150M

### SUPER S® CHERRY PICKER OIL

Super S® Cherry Picker Oil surpasses the minimum dielectric strength specification of 25kV making it suitable for use in high voltage electric service vehicles. Super S® Cherry Picker Oil is a premium high dielectric strength, high VI (viscosity index) anti-wear hydraulic oil developed for dependable performance in mobile, marine and industrial equipment, aerial platforms (man lifts) and bucket trucks, and emergency and electric service vehicles.

PRODUCT	PACKAGING	PART #
<b>CPicker 22</b>	5 Gal	SUS 230
<b>CPicker 32</b>	5 Gal	SUS 232
	55 Gal	SUS 232-55
<b>CPicker 68</b>	5 Gal	SUS 233



### SUPER S® WAYLUBE OIL

Super S® Waylube Oil are formulated for the unique lubrication requirements of slides and ways. They protect the slides and ways by providing excellent adhesion and metal wetting, load carrying capability, oxidation and thermal stability and corrosion resistance.

PRODUCT	PACKAGING	PART #
<b>ISO 68</b>	55 Gal	SUS 192-55
<b>ISO 220</b>	55 Gal	SUS 194-55

