Super S[®] Drip Oil

TECHNICAL PRODUCT INFORMATION



Super S Drip Oil

Super S Drip Oil is a formulated for once thru lubricant applications

FEATURES/ BENEFITS

Super S Drip Oil

- Provides moderate anti-wear protection
- Contains rust and corrosion preventatives
- Helps condition hoses and seals
- · Applied by dipping or pressure feed

APPLICATIONS

- · Irrigation pumps
- Sawmill once thru lubrication systems
- · Industrial chains and guides
- Moderately load open gear sets

SPECIAL HANDLING, NOTICES OR WARNINGS

Handle as you would any petroleum product

TYPICAL CHARACTERISTICS

Super S® Drip Oil		
Properties	Test Method ASTM-D	Data
Gravity, °API	1298	29
Flash Point °C/°F,	92	216/420
Pour Point °C/°F	97	-32/-25
Viscosity cSt @ 40°C cSt @ 100°C	445	32 4.95
Viscosity Index	2270	65
Color	1500	3.0

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 196 3/2 gallon bottles SUS 36DO 5 gallon pail SUS 37DO 55 gallon drum SUS 37DOTote 275 Gal Tote