

Super S[®] K-1 Kerosene



TECHNICAL PRODUCT INFORMATION

Super S K-1 Kerosene

Super S K-1 Kerosene is a low sulfur kerosene for heating and illumination

FEATURES/ BENEFITS

- Low Sulfur level suitable for indoor and un vented heater applications
- Clean burning in lanterns and stoves
- Good solvent for cleaning
- Removes oil, grease, and tar

RECOMMENDATIONS/SPECIFICATIONS

Meets or exceeds ASTM D-3699 for Low Sulfur Kerosene

APPLICATIONS

- Use in un-vented space heaters
- Lanterns
- Portable stoves
- Cleaning solvent for oil grease and tar

SPECIAL HANDLING, NOTICES OR WARNINGS

Product contacting the eye may cause irritation. Prolonged or repeated skin exposure causes mild irritation, dermatitis and defatting.

TYPICAL CHARACTERISTICS

Super S K-1 Kerosene		
Properties	Test Method ASTM D-	Data
Gravity, °API	1298	43.3
Flash Point °C/°F,	93	52/126
Density (lb/gal)	1298	6.74
Color, unfiltered saybolt	156	+22
Aromatics	1319	15.5
Viscosity, cSt @ 40 °C	445	1.43
Distillation °C/°F, IBP	86	334.9
5%		360.9
10%		369.9
30%		391.6
50%		417.2
70%		446.2
90%		481.5
95%		498.2
EP		513.9

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 186 5 gallon pail
SUS 187 55 gallon drum

Super S Lubricants

November 12, 2010

Super S and the Super S Shield are registered trademarks of Smitty's Supply, Inc. · © 2011 Smitty's Supply, Inc. All Rights Reserved.