

Super S[®] All Mileage Motor Oil

TECHNICAL PRODUCT INFORMATION



Super S All Mileage Motor Oil

Super S All Mileage Motor Oils are formulated with a special anti-wear additive system designed to protect both new and old engines.

FEATURES/ BENEFITS

Super S All Mileage Motor Oils are made with premium base stocks and proprietary additive system and they provide

- Protection for old and new engines
- Seal conditioning
- Low volatility base stocks to reduce oil consumption
- Extra detergency for cleaning the engine
- Enhanced deposit control to minimize compression loss
- Additional anti-wear protection for worn engine parts
- Available in 4 viscosity grades

APPLICATIONS

- Engines calling for API SP, SN Plus, SN / ILSAC GF-6A, GF-5, GF-4
- Both Low and high mileage engines
- Engines with high oil consumption
- It can be mixed with other synthetic and mineral oils
- Consult your owner's manual for the correct viscosity grade

RECOMMENDATIONS/SPECIFICATIONS

Super S All Mileage Motor Oils are recommended for applications calling for

- API Service Category SP, SN +, SN, SL
- ILSAC GF-6A, GF-5, GF-4

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling that you would use with petroleum products

TYPICAL CHARACTERISTICS

Super S® All Mileage Motor Oil					
Property	Test Method ASTM -D	SAE Viscosity Grade			
		5W-20	5W-30	10W-30	10W-40
Flash Point °C/ °F	D93	233/451	212/414	237/459	200/392
Pour Point °C/ °F	D97	-48/-54	-45/-49	-36/-33	-33/-27
Viscosity cSt @ 40°C cSt @ 100°C	D445	49.8	68.3	72.4	108.0
		8.5	11.1	10.8	15.7
VI	2270	149	155	137	154

Typical test data are average values only.
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SAE 5W20

SUS 1597 3/5Quart

SAE 10W30

SUS 1605 3/5Quart

SAE 5W30

SUS 1601 3/5Quart

SAE 10W40

SUS 1609 3/5Quart