



# Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3

**SAE 5W-30 API SP/ GF-6A**

**Super S® SuperSyn™ Full Synthetic dexos™ 1-Gen 3** is formulated with only premium full synthetic base stocks and advanced additive technology to provide the latest protection against **Low Speed Pre-Ignition (LSPI)** even in the most advanced turbo charged applications.

**Super S® dexos™1-Gen 3** motor oil allows turbo-charged and Gasoline Direct Inject Engines (GDI) that experience LSPI to safely maintain their efficiency and fuel economy performance and is the only GM Approved motor oil for 2011 and newer model gasoline engine cars and trucks and supersedes GM6094M, and GM4718M.

**Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** provides over 10% better fuel economy over traditional motor oils exceeding the performance requirements of API's Resource Conserving "SP" and car manufacturers' ILSAC GF-6A classification as well as all prior classifications providing the latest technology in fuel economy standards while also maintaining robust wear control, cleanliness, protection against sludge, and oxidation control.

Extended drain capable, **Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** was developed in part to keep your engine running longer. High quality synthetics like **Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** helps protect engines from loss of power caused by sludge and deposit build up. **Super S® dexos™1-Gen 3** keeps engines up to 60% cleaner than required by industry standards.

## FEATURES/BENEFITS

- Specifically designed to combat **Low Speed Pre-Ignition (LSPI)**
- Protection for small displacement **Turbo-Charged GDI Engines**
- Robust protection against sludge and piston deposit
- Latest technology in fuel economy; "Resource Conserving" approved
- Industry leading high temperature deposit control
- Extremely low volatility providing extended drain protection
- All new viscosity control and sheer technology maintains horsepower

## APPLICATIONS/APPROVALS

Recommended for use in applications calling for:

API SP and all prior classifications ILSAC GF-6A and prior classifications

Chrysler MS-6395  
 GMW17332, GMW16182, GM4718M,  
 GM6094M, GMW16076, GMW16181  
 Ford WSS-M2C960-A1 (SAE 5W-20)  
 Ford WSS-M2C961-A1 (SAE 5W-30)  
 Ford WSS-M2C962-A1 (SAE 0W-20)  
 Ford WSS-M2C963-A1 (SAE 0W-30)  
 Ford WSS-M2C945-B1 (SAE 5W-20)  
 Ford WSS-M2C946-B1 (SAE 5W-30)  
 Ford WSS-M2C947-B1 (SAE 0W-20)  
 Ford WSS-M2C953-B1 (SAE 0W-30)  
 Honda/Acura HTO-06

*Generation 3 dexos 1™ engine oils show considerable improvements in the areas of fuel economy, deposit formation in TGD engines, and eliminating LSPI events.*



**Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3**  
**SAE 5W-30 API SP/ GF-6A**

**TYPICAL CHARACTERISTICS**

<b>SuperS® SuperSyn™ dexos™1-Gen 3</b>		
<i>PROPERTIES</i>	<i>TEST METHOD ASTM D-</i>	<i>TYPICAL RESULTS</i>
SAE Viscosity Grade		5W-30
Flash Point °C	92	233/451
Pour Point °C	97	-39/-38
Viscosity @ 40°C @ 100°C	445	60.5 10.6
Viscosity Index	2270	173
TBN		8.0
Color		3.0

The above characteristics are typical of current production. While production will conform to Smitty's specification, slight variations may occur and do not affect performance. For a complete list of applications, contact your SuperS® Representative.

**PRODUCT NUMBERS**

5W-30	Pkg Size
SUS 799	6/1QT
SUS 799-35	3/5QT
SUS 6799	6gal
SUS 799-55	55gal
SUS 799 TOTE	TOTE
SUS 799 BULK	BULK

**Brand License number for Super S SuperSyn™ dexos™1 Gen3  
 Full Synthetic SAE 5W-30 is: D330AAEB016**

**Special Handling, Notices, or Warnings**

Avoid contact with skin. Rinse with soap and water immediately after skin contact. This product is unlikely to present and significant health hazards. Dispose of used oil properly.