

SuperSyn™ Premium Full Synthetic CVT Fluid

TECHNICAL PRODUCT INFORMATION



SuperSyn® Premium Full Synthetic CVT Fluid is a full synthetic transmission fluid combined with a highly sophisticated additive package specially formulated to provide robust protection for the steel components in vehicles equipped with either chain or push belt continuously variable transmissions. This fluid is suitable for use as a service fill fluid for all CVT's coupled with engine displacement sizes 3.5 liters or less.

SuperSyn® Premium Full Synthetic CVT Fluid's strong oil film and sheer stability provides optimum protection against shudder commonly associated with CVT transmissions. Extends belt, chain, and pulley life by placing a film layer between the metal-to-metal contact points that cause wear. New, unique formula has excellent thermal and oxidation stability providing you more protection for more miles than ever before.

Recommendations

- Superior anti-shudder durability for enhanced driving comfort
- Balanced formulation for high torque capacity
- Superior Anti-Wear Protection to provide long service life
- Balanced formulation for high torque capacity
- Compatibility in multiple CVT transmission types
- Patented Technology designed to exceed performance requirements of the major Asian OEM's
- Longer life and service interval than leading competitors based on Vehicle Mileage Accumulation Test

TYPICAL CHARACTERISTICS

| SuperSyn Premium CVT | |
|----------------------|-----------|
| Properties | Data |
| Appearance | Typical |
| Pour Point | -50°C |
| Flash Point | 206°C |
| Viscosity @ 40°C | 36.95 cSt |
| Viscosity @ 100 °C | 7.5 cSt |
| Viscosity Index | 176 |
| Gravity, API | 32.8 |
| Brookfield -40°C | 12,000 |



PRODUCT NUMBERS

- SUS 229 12/1qt bottles
- SUS 229-55 55 gal drum

SuperSyn™ Premium Full Synthetic CVT Fluid



TECHNICAL PRODUCT INFORMATION

TECHNICAL PRODUCT INFORMATION

SuperSyn™ Premium Full Synthetic CVT Fluid is suitable for the following manufacturers if the engine is 3.5l or less:

| |
|--|
| Audi Multitronic |
| BMW Mini Cooper EZL 799A/ 83 22 0 136 376/ 83 22 0 429 154 |
| Chery CVT |
| Chery WCF-1/Shell SL 2100 |
| Citroen PSA Standard 9735EF |
| Daihatsu AMMIX CVTF DFE |
| Daihatsu AMMIX CVT Fluid DC |
| Daihatsu AMMIX CVT Fluid DFC |
| Daihatsu Fluid TC |
| Dodge/Jeep/Chrysler NS-2 |
| Dodge/Chrysler/Jeep/Mopar CVT+4 |
| Fiat Tutela Car CVT NG |
| Fujjyuuko i-CVTF FG |
| GM/Saturn DEX-CVT, GM 1940713 and 1940714 |
| GM/Saturn CVTF I-Green2 |
| GM VT40 /GM HP CVT |
| Honda HMMF (without starting clutch) |
| Honda HCF2 |
| Honda Z-1 (CVT without starting clutch) |
| Honda CVT (not recommended for any Honda with starting clutch) |
| Honda Ultra HEVF-Type 1 |
| Hyundai/Kia CVT-1 |
| Hyundai/Kia SP III (CVT model) |
| Idemitsu CVTF-EX1 |
| Lexus Fluid TC, Fluid FE |
| Mazda JWS 3320 |
| MG Rover EM-CVT |
| Mini Cooper EZL 799/EZL 799A/ZF CVT V1 |

| |
|---|
| Mitsubishi CVT Fluid-MA1 |
| Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1) |
| Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+) |
| Mitsubishi CVTF ECO J4 |
| Mitsubishi (Diaqueen) SP-III (CVT model only) |
| Nissan NS-1 |
| Nissan NS-2 |
| Nissan NS-2V |
| Nissan NS-3 |
| Nissan N-CVT |
| Opel/Vauxhall 7-speed CVT, 95529854 |
| Perodua D-CVT |
| Peugeot PSA Standard 9735EF |
| Punch CVTF-EX1 for Punch VT2/VT3 Transmissions |
| Renault Elf Matic CVT |
| Renault CVT CK/SK/FK |
| Shell Green 1V |
| Peugeot PSA Standard 9735EF |
| Subaru iCVT |
| Subaru iCVT FG |
| Subaru ECVT |
| Subaru Lineartronic chain CVT and CVT II Fluid, K0425Y0710 & K0425Y0711 |
| Subaru Lineartronic chain CVT 3 Fluid |
| Subaru Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700 |
| Subaru High Torque CVTF-LV |
| Suzuki CVTF TC |

SuperSyn™ Premium Full Synthetic CVT Fluid

TECHNICAL PRODUCT INFORMATION



| |
|-------------------------------|
| Suzuki CVTF 3320 |
| Suzuki CVTF 4401 |
| Suzuki NS-2 |
| Suzuki CVT Green 1 & 2 |
| Suzuki CVT Green 1V |
| Toyota CVTF TC |
| Toyota CVTF FE |
| Volvo CVT 4959 |
| VW/Audi TL 521 16 (G 052 516) |
| VW/Audi TL 521 80 (G 052 180) |

| |
|--|
| Zotye CVTs |
| eMobility Claims/Applications |
| Ford Escape Hybrid with eCVT |
| Honda e:HEV |
| Honda iMMD |
| Jatco CVT 8 Hybrid |
| Mazda SKYACTIVE-HYBRID |
| Nissan Altima Hybrid |
| Toyota THSII/Toyota Prius |
| Toyota THS 5th Gen. / Toyota Noah, Voxy etc. |

Not to be used for DCT applications This claim sheet supersedes any previous versions prior to January 9, 2024