

# Super S<sup>®</sup> Premium Universal Tractor Hydraulic Fluid

## TECHNICAL PRODUCT INFORMATION



### Super S Premium Universal Tractor Hydraulic Fluid

**Super S Premium Universal Tractor Hydraulic Fluid** is premium multi-functional fluid used as hydraulic medium, a power steering, a power brake, power take off (PTO) and implement drive fluid.

#### FEATURES/ BENEFITS

##### Super S Premium Universal Tractor Hydraulic Fluid

- Superior detergent/dispersant package keeps system cleaner for longer life
- Lubricate the transmission, differential, and final drive gears in tractors and implements
- Provides extreme pressure and anti wear protection
- Protects against rust and corrosion,
- Prevents seal and pump deterioration
- Protect tractor transmission, axles and hydraulic pumps,
- Eliminate brake chatter
- Controlled frictional characteristics which permit the wet brakes to hold properly and allow smooth engagement of power take off (PTO) clutches.

#### APPLICATIONS

**Super S Premium Universal Tractor Hydraulic Fluid** has been field-tested and is suitable for use where any of the following fluids are recommended:

- AGCO 821XL
- ALLISON C2, C3, C4
- CATERPILLAR TO-2
- CNH MAT 3505, 3510, 3525, 3526 (All Season), 3540
- DENISON HF-0, HF-1, HF-2 (except demulsibility)
- DEUTZ-ALLIS POWER FLUID 821XL, 25741, 25743, 246634, 272843
- DRESSER –
- FIAT HESTON AF-87
- FORD ESN-M2C-86 A-C, FNHA-2-C-200, FNHA-2-C-201, M2CA-C, ESN-M2C134A-D (NH-410B), ESN-M2C86A, B, & C, ESN-M2C-41, 41A & B, & 43, ESN-M2C-48 B & C, ESN-M2C53 A & B, ESN-M2C-77A, 78A, 79A, ESN-M2C-142A, ESN-M2C-143, ESN-M2C-92A, ESN-M2C-159 A-C, New Holland M4864 A & B, New Holland 82948718
- INDUSTRY OF MACHINERY AND TRACTORS (IMT)
- INTERNATIONAL HARVESTER HY-TRAN B-6
- CASE IH HY-TRAN B-6, CASE-O-MATIC TYPE A, MS-143, 144, 145 INTERNATIONAL FAMALL (TCH FLUID), MS-185 (TFD FLUID), MS1204-1205 (POWERGARD PFT), MS1206 (POWERGARD PFT), MS1207, MS1209 (HYTRAN ULTRA OR MULTITRAN), MS1210, MS-1216, MS-1230 (POCLAIN EQUIPMENT), MS-1317
- JOHN DEERE JTD 303, J14A-C, J20A, J20B, J20C, J21A
- KIOTI TRACTOR
- KOMATSU-DRESSER B06.0002
- KUBOTA UDT, Super UDT
- LANDINI TRACTOR
- LEYLAND FOR UTTO ONLY TRACTOR
- MASSEY FERGUSON 1103A & B, M1110, 1127, 1127 A&B, M1129, M1129A (PERMATRAN), M1135 (PERMATRAN III), M1138, M1141, M1143, M1139 (STOU), M1144 (STOU), M1145
- PARKER (DENISON UTTO) HF-0, HF-1, HF-2
- QUATROL THF BRAND
- RENK-DOROMAT 87.3 & 874A/B
- STEIGER HTF (SEMS 17001)
- VALMET TRACTOR
- VALTRACTORES –
- VERSATILE GEAR AND HYDRTRANS FLUID 23M & 24M
- VICKERS 35VQ25, PUMP TEST
- WHITE/MINNEAPOLIS-MOLINE/55, 5J, Q-1705, Q-1722, Q-1766, Q-1766B, Q-1802, Q-1826
- YANMAR TRACTOR

**SPECIAL HANDLING, NOTICES OR WARNINGS**

Use the same care and handling that you would use with petroleum products.

**TYPICAL CHARACTERISTICS**

<b>Super S Premium Universal Tractor Hydraulic Fluid</b>		
<i>Properties</i>	<i>Test Method ASTM D-</i>	<i>Data</i>
SAE Grade		10W-30
API	1298	GL-4
Flash Point °C/°F,	92	204/400
Pour Point °C/°F,	97	-42/-43.6
Color	1500	
Viscosity cSt @ 40°C cSt @ 100°C	445	53 9.2
Viscosity Index	2270	135

Typical test data are average values only.  
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

**PRODUCT NUMBERS**

- SUS 236                    5 gallon pail
- SUS 236-55            55 Gallon Drum
- SUS 236tote            275 gal. tote
- SUS 237bulk            Bulk