

Super S[®] Bar & Chain Oil

TECHNICAL PRODUCT INFORMATION



Super S Bar & Chain Oil

Super S Bar & Chain Oil is formulated with virgin mineral oil and specific additives for today's high speed chain saws

FEATURES/ BENEFITS

- Formulated with high quality base oils and a balanced additive package
- Different base oil viscosities: summer and winter
- High Tac no sling additive helps keep chain lubricated
- EP (extreme pressure) additives lubricate under heavy load and shock load conditions
- Penetrates the chain: provides start up lubrication
- Resists wear in service
- Resists corrosion in storage

APPLICATIONS

- **Super S Bar and Chain Oil** is designed for use in:
- Residential, commercial and industrial chain saws
- Hand operated and automatic oilers
- Adverse operating conditions of the forest products industry
- Chains, bars, and sprockets

RECOMMENDATIONS/SPECIFICATIONS

- All types of chain saws

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

TYPICAL CHARACTERISTICS

Super S Bar & Chain Oil			
Properties	Test Method ASTM D-	Data	
		Summer	Winter
Gravity, °API	1298		
Flash Point °C/°F,	92	218/425	210/410
Pour Point °C/°F	97	-24/-10	-29/-20
Color	1500	4	4
Viscosity SUS @ 100°F	88	630	300

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 90-6	6/1 quart bottles
SUS 20-3	3/1 gallon bottles
SUS 19	55 gallon drum
SUS 19 Bulk	Bulk