

Super S[®] Hydraulic Jack Oil

TECHNICAL PRODUCT INFORMATION



Super S Hydraulic Jack Oil

Super S Hydraulic Jack Oil is formulated with selected base oils and additives to meet the lubrication needs of hydraulic jacks, snow plows and other hydraulic systems

FEATURES/ BENEFITS

Super S Hydraulic Jack Oil

- Provides wear protection for moving parts
- Resists foaming
- Inhibits oxidation and degradation of the oil
- Controls rusting and corrosion of equipment
- Mixes with standard hydraulic jack fluids
- Available in 12 oz bottles for use on small hydraulic systems

APPLICATIONS

- Hydraulic Jacks
- Snow Plows
- Refillable shock absorbers
- Other applications calling for an anti wear hydraulic oil

SPECIAL HANDLING, NOTICES OR WARNINGS

Handle as you would any petroleum product

TYPICAL CHARACTERISTICS

Super S [®] Hydraulic Jack Oil		
<i>Properties</i>	<i>Test Method ASTM D-</i>	<i>Data</i>
ISO Viscosity Grade		32
SAE Grade		10
Gravity, °API	1298	31.0
Flash Point °C/°F,	92	204/400
Pour Point °C/°F,	97	-29/-20
Color	1500	2.0
Viscosity cSt @ 40°C cSt @ 100°C	445	33.0
Viscosity Index	2270	

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 146

12/12oz bottles