



Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3

SAE 0W-20 API SQ/ GF-7A

Super S® SuperSyn™ Full Synthetic dexos™ 1-Gen 3 is

formulated with only premium full synthetic base stocks and advanced additive technology to provide the latest protection against **Low-Speed Pre-Ignition (LSPI)** even in the most advanced turbo charged applications.

Super S® dexos™1-Gen 3 motor oil allows turbo-charged and Gasoline Direct Inject Engines (GDI) that experience LSPI to safely maintain their efficiency and fuel economy performance and is the only GM Approved motor oil for 2011 and newer model gasoline engine cars and trucks and supersedes GM6094M, and GM4718M.

Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3

provides over 10% better fuel economy over traditional motor oils exceeding the performance requirements of API's Resource Conserving "SQ" and car manufacturers' ILSAC GF-7A classification as well as all prior classifications providing the latest technology in fuel economy standards while also maintaining robust wear control, cleanliness, protection against sludge, and oxidation control.

Extended drain capable, **Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** was developed in part to keep your engine running longer. High quality synthetics like **Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** helps protect engines from loss of power caused by sludge and deposit build up. **Super S® dexos™1-Gen 3** keeps engines up to 60% cleaner than required by industry standards.

FEATURES/BENEFITS

- Excellent for passenger cars, light duty trucks, SUVs, and gas/electric hybrid vehicles
- Protects turbo-charged engines against LSPI (Low Speed Pre-Ignition)
- Prolongs engine life by extending drain intervals
- Excellent protection under severe operating conditions
- Controls sludge and high temperature deposits from forming

APPLICATIONS/APPROVALS

Recommended for use in applications calling for:

API SQ and all prior classifications ILSAC GF-7A and prior classifications

- When licensed GM dexos1™ - Gen 3 is required
- When API SQ, SP, SN Plus, and SN oils are required
- When ILSAC GF-6A, GF-5, and GF-4 oils are required
- When GM 17332, GMW 16182, GM 4718M, GM 6094M, GMW 16076, GMW 16181 is required
- When Ford WSS-M2C972-A1 and Ford WSS-M2C962-A1 is required
- When Chrysler MS-6395 is required
- When Honda/Acura HTO-06 is required
- In naturally aspirated gasoline engines and turbo-charged engines

Generation 3 dexos 1™ engine oils show considerable improvements in the areas of fuel economy, deposit formation in TGDI engines, and eliminating LSPI events.



Super S[®] SuperSyn[™] Full Synthetic dexos[™]1-Gen 3

SAE 0W-20 API SQ/ GF-7A

TYPICAL CHARACTERISTICS

SuperS [®] SuperSyn [™] dexos [™] 1-Gen 3		
PROPERTIES	TEST METHOD ASTM D-	TYPICAL RESULTS
SAE Viscosity Grade		0W-20
Flash Point °C	92	225/437
Pour Point °C	97	-45/-49
Viscosity @ 40°C @ 100°C	445	44.2 8.4
Viscosity Index	2270	171
TBN		7.8
Color		2.8

The above characteristics are typical of current production. While production will conform to Smitty's specification, slight variations may occur and do not affect performance. For a complete list of applications, contact your SuperS[®] Representative.

PRODUCT NUMBERS

0W-20	Pkg Size
SUS 797	6/1QT
SUS 79705	3/5QT
SUS 6797	6gal
SUS 797-55	55gal
SUS 797 TOTE	TOTE
SUS 797 BULK	BULK

Special Handling, Notices, or Warnings

Avoid contact with skin. Rinse with soap and water immediately after skin contact. This product is unlikely to present and significant health hazards. Dispose of used oil properly.