

Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3

SAE 5W-30 API SQ/ GF-7A



Super S® SuperSyn™ Full Synthetic dexos™ 1-Gen 3 is

formulated with only premium full synthetic base stocks and advanced additive technology to provide the latest protection against **Low-Speed Pre-Ignition (LSPI)** even in the most advanced turbo charged applications.

Super S® dexos™1-Gen 3 motor oil allows turbo-charged and Gasoline Direct Inject Engines (GDI) that experience LSPI to safely maintain their efficiency and fuel economy performance and is the only GM Approved motor oil for 2011 and newer model gasoline engine cars and trucks and supersedes GM6094M, and GM4718M.

Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3

provides over 10% better fuel economy over traditional motor oils exceeding the performance requirements of API's Resource Conserving "SQ" and car manufacturers' ILSAC GF-7A classification as well as all prior classifications providing the latest technology in fuel economy standards while also maintaining robust wear control, cleanliness, protection against sludge, and oxidation control.

Extended drain capable, **Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** was developed in part to keep your engine running longer. High quality synthetics like **Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3** helps protect engines from loss of power caused by sludge and deposit build up. **Super S® dexos™1-Gen 3** keeps engines up to 60% cleaner than required by industry standards.

FEATURES/BENEFITS

- Specifically designed to combat **Low Speed Pre-Ignition (LSPI)**
- Protection for small displacement **Turbo-Charged GDI Engines**
- Robust protection against sludge and piston deposit
- Latest technology in fuel economy; "Resource Conserving" approved
- Industry leading high temperature deposit control
- Extremely low volatility providing extended drain protection
- All new viscosity control and sheer technology maintain horsepower

APPLICATIONS/APPROVALS

Recommended for use in applications calling for:

API SQ and all prior classifications ILSAC GF-7A and prior classifications

- Chrysler MS-6395 When licensed GM dexos1™ - Gen 3 is required
- When API SQ, SP, SN Plus, and SN oils are required
- When ILSAC GF-6A, GF-5, and GF-4 oils are required
- When GM 17332, GMW 16182, GM 4718M, GM 6094M, GMW 16076, GMW 16181 is required
- When Ford WSS-M2C972-A1 and Ford WSS-M2C962-A1 is required
- When Chrysler MS-6395 is required
- When Honda/Acura HTO-06 is required
- In naturally aspirated gasoline engines and turbo-charged engines

Generation 3 dexos 1™ engine oils show considerable improvements in the areas of fuel economy, deposit formation in TGDI engines, and eliminating LSPI events.

March 10, 2026

Super S® and the Super S® Shield are registered trademarks of Smitty's Supply, Inc. • © 2011 Smitty's Supply, Inc. All Rights Reserved.

Super S® SuperSyn™ Full Synthetic dexos™1-Gen 3
SAE 5W-30 API SQ/ GF-7A



TYPICAL CHARACTERISTICS

SuperS® SuperSyn™ dexos™1-Gen 3		
<i>PROPERTIES</i>	<i>TEST METHOD ASTM D-</i>	<i>TYPICAL RESULTS</i>
SAE Viscosity Grade		5W-30
Flash Point °C	92	225/437
Pour Point °C	97	-45/-49
Viscosity @ 40°C @ 100°C	445	44.2 8.4
Viscosity Index	2270	171
TBN		7.8
Color		2.8

The above characteristics are typical of current production. While production will conform to Smitty's specification, slight variations may occur and do not affect performance. For a complete list of applications, contact your Super S® Representative.

PRODUCT NUMBERS

5W-30	Pkg Size
SUS 799	6/1QT
SUS 799-35	3/5QT
SUS 6799	6gal
SUS 799-55	55gal
SUS 799 TOTE	TOTE
SUS 799 BULK	BULK

Special Handling, Notices, or Warnings

Avoid contact with skin. Rinse with soap and water immediately after skin contact. This product is unlikely to present and significant health hazards. Dispose of used oil properly.